

### **AMENDMENTS TO THE SPECIFICATION**

Please replace paragraph [0023] with the following amended paragraph:

[0023] The injector body 4 of the fuel injection device 1 contains a pressure booster 11. The pressure booster 11 includes a working chamber labeled with the reference numeral 12, which can be acted on with highly pressurized fuel via an inlet 13 branching from the high-pressure line 3. The pressure booster 11 has a pressure booster piston 14 that has a first end 15 oriented toward the working chamber 12 and a second end 16 oriented toward a differential pressure chamber 17. At the second end 16, the pressure booster piston 14 rests against a return spring 18, which in turn rests against an annular surface inside the second housing part 9 of the injector body 4. The pressure booster piston 14 of the pressure booster 11 acts on a high-pressure chamber 19 contained in the lower region of the second housing part 9 **and defined, at least in part, by an end face 14a of the pressure booster piston 14.** When the end of the pressure booster piston 14 oriented toward the high-pressure chamber 19 travels inward, the fuel contained in this chamber is compressed even more as a function of the boosting ratio of the pressure booster 11, and flows into a control chamber 20 and into a nozzle chamber 23 contained in the injector housing 10 via a nozzle chamber inlet 22. The nozzle chamber 23 encloses the injection valve element 24 of the fuel injection device in a region in which a pressure shoulder is provided on the injection valve element 24. An annular gap extends from the nozzle chamber 23 to the end of the fuel injection device 1 oriented toward the combustion chamber. Via the annular gap, injection openings 25 at the combustion chamber end of the fuel injection device 1 are acted on with fuel. These injection openings are unblocked with a vertical movement of

Appl. No. 10/531,166  
Amdt. dated April 25, 2008  
Reply to Office action of Jan. 25, 2008

the injection valve element 24 so that highly pressurized fuel can be injected via the injection openings 25 into a combustion chamber 26 of an autoignition internal combustion engine.